

A Toyota Group Company



XZU342L

HINO300 SERIES







| Α | Toyota | Group | Company |
|---|--------|-------|---------|
|---|--------|-------|---------|

| MODELO                    | XZU342L  |             |  |  |  |
|---------------------------|--|-------------|--|--|--|
| MODELS                    | XZU342LC   | XZU302LM    | XZU342LH                                   |  |  |
| DRIVE SYSTEM              | 4 x 2 (4W)   | 4 >         | x 2 (6W)                                   |  |  |
| CAB                       | Narrow Cab   |             |  |  |  |
| GROSS VEHICLE WEIGHT (Kg) | 3,800  | 4,460       | 7,500                                      |  |  |
| TRANSMISSION              | 5-Speed M/T with Overdrive   |             |  |  |  |
| TIRES & RIMS              | 7.50-15-12PR 7.50-16-14PR  |             |  |  |  |
| FUEL TANK CAPACITY (L)    | 100  |             |  |  |  |
| DIMENSIONS                |  |             |  |  |  |
| Wheelbase (mm)            | 3,405  | 3,380       |  |  |  |
| Length (mm)               | 6,430  | 6320        |  |  |  |
| Width (mm)                | 1,720  | 1,720 1,955 |  |  |  |
| Height (mm)               | 2,115  | 2,115 2,155 |  |  |  |
| ENGINE                    |  |             |  |  |  |
| Model                     | N04C-VC  |             |  |  |  |
| Emission Standard         | Euro 4   |             |  |  |  |
| Max. Engine Speed (rpm)   | 3,100  |             |  |  |  |
| Туре                      | Diesel, 4-Cycle, Vertical, Inline, 4-Cylinder, Overhead Valve, Water-cooled            |             |  |  |  |
| Combustion System         | Direct Injection Type  |             |  |  |  |
| Fuel Injection System     | Electronic Control Common Rail Type  |             |  |  |  |
| Displacement (L)          | 4.009  |             |  |  |  |
| PERFORMANCE               |  |             |  |  |  |
| Max. Output (PS) ISO      | 136  |             |  |  |  |
| Max. Torque (Nm) ISO      | 390  |             |  |  |  |
| Max. Speed (kph)          | 134  | 118         |  |  |  |
| SUSPENSION                |  |             |  |  |  |
| Front                     | Semi-elliptic Leaf Springs with Double Action Shock Absorbers                          |             |  |  |  |
| Rear                      | Semi-elliptic Leaf Springs with Double Action Shock Absorbers Semi-elliptic Main and A |             | Springs with Double Action Shock Absorbers |  |  |
| BRAKES                    |  |             |  |  |  |
| Service (Type)            | Hydraulic System, Dual-Circuit, Vacuum Assist  |             |  |  |  |
| (Features)                | 2 Leading Shoes for Front and Rear Wheels  |             |  |  |  |
| Parking                   | ing Mechanical, Internal Expanding, Acting on Transmission Output Shaft                |             |  |  |  |



