

A Toyota Group Company



XZU600L

HINO300 SERIES







Α	Toy	ota G	iroup	Com	pany
---	-----	-------	-------	-----	------

MODELS	XZU600L						
	XZU600LA	XZU600LM					
DRIVE SYSTEM	4 x 2 (4W)						
CAB	Narrow Cab						
GROSS VEHICLE WEIGHT (Kg)	4,490						
TRANSMISSION	6-Speed A/T with Overdrive						
TIRES & RIMS	7.00R16-12PR						
FUEL TANK CAPACITY (L)	80						
POWER DOOR & WINDOW	Equipped						
POWER DOOR LOCK	Equipped						
DIMENSIONS							
Wheelbase (mm)	2,525						
Length (mm)	4,680						
Width (mm)	1,695						
Height (mm)	2,130						
ENGINE							
Model	N04C-WJ						
Emission Standard	Euro 4						
Max. Engine Speed (rpm)	3,100						
Туре	Diesel, 4-Cycle, Vertical, Inline, 4-Cylinder, Overhead Valve, Water-cooled						
Combustion System	Direct Injection Type						
Fuel Injection System	Electronic Control Common Rail Type						
Displacement (L)	4.009						
PERFORMANCE							
Max. Output (PS) ISO	136						
Max. Torque (Nm) ISO	390						
Max. Speed (kph)	125						
SUSPENSION							
Front	Semi-elliptic Tapered Leaf Springs v	with Double Action Shock Absorbers					
Rear	Semi-elliptic Main and Auxiliary Leaf Springs with Double Action Shock Absorbers						
BRAKES							
Service (Type)	Hydraulic System, Dual	-Circuit, Vacuum Assist					
(Features)	Front: Disc Brake Rear: Drum Brake with Auto Brakeshoe Adjuster, Equipped with ABS						
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft						



