



FC9JL7A

HINO500 SERIES







A Toyota Group Company

MODEL	FC9JL7A
	Cargo
DRIVE SYSTEM	4 x 2 (6W)
GROSS VEHICLE WEIGHT (Kg)	10,400
GROSS COMBINATION MASS (Kg)	N/A
TRANSMISSION	6-Speed, Overdrive, Synchromesh 2nd - 6th
TIRES & RIMS	8.25R16-14PR
FUEL TANK CAPACITY (L)	200
DIMENSIONS	
Wheelbase (mm)	4,990
Length (mm)	8,395
Width (mm)	2,190
Height (mm)	2,470
ENGINE	
Model	J05E-TY
Emission Standard	Euro 4
Max. Engine Speed (rpm)	2,700
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Inline, 4-Cylinder, Overhead Camshaft, Water-cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	5.123
PERFORMANCE	
Max. Output (PS) ISO	210
Max. Torque (Nm) ISO	637
Max. Speed (kph)	115
SUSPENSION	
Front	Semi-elliptic Leaf Springs with Single Action Shock Absorbers
Rear	Semi-elliptic Leaf Springs with Single Action Shock Absorbers
BRAKES	
Service (Type)	Air Over Hydraulic, Dual-Circuit, Equipped with ABS
(Features)	2 Leading Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft



