



FG8JP7A

HINO500 SERIES







A Toyota Group Company

MODEL	FG8JP7A	
DRIVE SYSTEM	Cargo 4 x 2 (6W)	
GROSS VEHICLE WEIGHT (Kg)	16,000	
GROSS COMBINATION MASS (Kg)	N/A	
TRANSMISSION	6-Speed, Overdrive, Synchromesh 2nd - 6th	
TIRES & RIMS	11R22.5-16PR	
FUEL TANK CAPACITY (L)	200	
DIMENSIONS		
Wheelbase (mm)	5,530	
Length (mm)	9,485	
Width (mm)	2,490	
Height (mm)	2,745	
ENGINE		
Model	J08E-WF	
Emission Standard	Euro 4	
Max. Engine Speed (rpm)	2,600	
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled	
Combustion System	Direct Injection Type	
Fuel Injection System	Electronic Control Common Rail Type	
Displacement (L)	7.684	
PERFORMANCE		
Max. Output (PS) ISO	240	
Max. Torque (Nm) ISO	716	
Max. Speed (kph)	104	
SUSPENSION		
Front	Semi-elliptic Tapered Leaf Springs (Reinforced Type) with Double Action Shock Absorbers	
Rear	Semi-elliptic Main and Auxiliary Leaf Springs (Reinforced Type)	
BRAKES		
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS	
(Features)	Leading and Trailing Shoes for Front and Rear Wheels	
Parking	Air-operated Spring Brake Acting on Rear Axle	



