



FM8JR7A

HINO500 SERIES







A Toyota Group	o Company
----------------	-----------

MODEL	FM8JR7A	
DRIVE SYSTEM	Cargo 6 x 4 (10W)	
GROSS VEHICLE WEIGHT (Kg)	28.000	
	N/A	
GROSS COMBINATION MASS (Kg)		
TRANSMISSION	9-Speed, Synchromesh, Direct-drive	
TIRES & RIMS	11.00R20-16PR	
FUEL TANK CAPACITY (L)	200	
DIMENSIONS		
Wheelbase (mm)	4,630 + 1,350	
Length (mm)	9,485	
Width (mm)	2,490	
Height (mm)	2,765	
ENGINE		
Model	J08E-WD	
Emission Standard	Euro 4	
Max. Engine Speed (rpm)	2,600	
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled	
Combustion System	Direct Injection Type	
Fuel Injection System	Electronic Control Common Rail Type	
Displacement (L)	7.684	
PERFORMANCE		
Max. Output (PS) ISO	280	
Max. Torque (Nm) ISO	824	
Max. Speed (kph)	98	
SUSPENSION		
Front	Semi-elliptic Leaf Springs (Reinforced Type) with Single Action Shock Absorbers	
Rear	Semi-elliptic Leaf Springs (Reinforced Type)	
BRAKES		
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS	
(Features)	Leading and Trailing Shoes for Front and Rear Wheels	
Parking	Air-operated Spring Brake Acting on Front and 1st Rear Axle	



