

FY2P

HINO700 SERIES







A Toyota Group Company

MODELS	FY2PWUD Dump	FY2P FY2PUUM Mixer	FY2PYUA Cargo
DRIVE SYSTEM	8 x 4 (12W)		
GROSS VEHICLE WEIGHT (Kg)	39,400		
GROSS COMBINATION MASS (Kg)	N/A		
TRANSMISSION	12-Speed, Overdrive, Synchromesh 1st - 12th		
TIRES & RIMS	295/80R22.5		
FUEL TANK CAPACITY (L)	266 400		
DIMENSIONS			
Wheelbase (mm)	1,850 + 3,850 + 1,410	1,850 + 3,400 + 1,410	1,850 + 4,300 + 1,410
Length (mm)	10,080	9,430	11,800
Width (mm)	2,490		
Height (mm)	3,100		3,570
ENGINE			
Model	P11C-VB		
Emission Standard	Euro 4		
Max. Engine Speed (rpm)	2,400		
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Valve, Water-cooled		
Combustion System	Direct Injection Type		
Fuel Injection System	Electronic Control Common Rail Type		
Displacement (L)	10.520		
PERFORMANCE			
Max. Output (PS) ISO	373		
Max. Torque (Nm) ISO	1,565		
Max. Speed (kph)	121		129
SUSPENSION			
Front	Semi-elliptic Leaf Springs with Shock Absorbers and Stabilizer		
Rear	Semi-elliptic Leaf Springs with Torque Rods		
BRAKES			
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type		
(Features)	Leading and Trailing Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster and ABS		
Parking	Spring Brake Acting on Rear Wheels		



