

SH1EESA

HIN0700 SERIES







A Toyota Group Company

	SH1EESA
MODEL	
DRIVE SYSTEM	Tractor Head 4 x 2 (6W)
GROSS VEHICLE WEIGHT (Kg)	19,500
GROSS COMBINATION MASS (Kg)	45,500
TRANSMISSION	7-Speed, Overdrive, Synchromesh 2nd - 7th
TIRES & RIMS	295/80R22.5-16PR
FUEL TANK CAPACITY (L)	400
DIMENSIONS	400
Wheelbase (mm)	3,300
Length (mm)	5,695
Width (mm)	2,490
Height (mm)	2,975
ENGINE	2,010
Model	E13C-UN
Emission Standard	Euro 4
Max. Engine Speed (rpm)	2,130
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	12.913
PERFORMANCE	
Max. Output (PS) ISO	410
Max. Torque (Nm) ISO	1,863
Max. Speed (kph)	117
SUSPENSION	
Front	Semi-elliptic Tapered Leaf Springs with Shock Absorbers
Rear	Semi-elliptic Main and Auxiliary Leaf Springs with Shock Absorbers
BRAKES	
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type
(Features)	Leading and Trailing Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster and ABS



