



SS1EKSA

HINO700 SERIES







A Toyota Group	Company
----------------	---------

MODEL	SS1EKSA	
	Tractor Head	
DRIVE SYSTEM	6 x 4 (10W)	
GROSS VEHICLE WEIGHT (Kg)	28,300	
GROSS COMBINATION MASS (Kg)	60,000	
TRANSMISSION	16-Speed, Overdrive, Synchromesh 1st - 16th	
TIRES & RIMS	295/80R22.5-16PR	
FUEL TANK CAPACITY (L)	400	
DIMENSIONS		
Wheelbase (mm)	3,300 + 1,310	
Length (mm)	7,005	
Width (mm)	2,490	
Height (mm)	3,325	
ENGINE		
Model	E13C-UR	
Emission Standard	Euro 4	
Max. Engine Speed (rpm)	2,130	
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled	
Combustion System	Direct Injection Type	
Fuel Injection System	Electronic Control Common Rail Type	
Displacement (L)	12.913	
PERFORMANCE		
Max. Output (PS) ISO	450	
Max. Torque (Nm) ISO	1,912	
Max. Speed (kph)	125	
SUSPENSION		
Front	Semi-elliptic Tapered Leaf Springs with Shock Absorbers	
Rear	SemSemi-elliptic Tapered Leaf Springs with Shock Absorbers and Torque Rods	
BRAKES		
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type	
(Features)	Leading and Trailing Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster and ABS	
Parking	Spring Brake Acting on Front and Rear Frontward Wheels	



