

A Toyota Group Company



SS2PKUA

HIN0700 SERIES







Α	Toyota	Group	Company
---	--------	-------	---------

	SSORIIA			
MODEL	SS2PKUA			
	Tractor Head			
DRIVE SYSTEM	6 x 4 (10W)			
GROSS VEHICLE WEIGHT (Kg)	N/A			
GROSS COMBINATION MASS (Kg)	60,000			
TRANSMISSION	16-Speed, Overdrive, Synchromesh 1st - 16th			
TIRES & RIMS	295/80R22.5			
FUEL TANK CAPACITY (L)	400			
DIMENSIONS				
Wheelbase (mm)	3,150 + 1,410			
Length (mm)	6,780			
Width (mm)	2,490			
Height (mm)	3,505			
ENGINE				
Model	P11C-VB			
Emission Standard	Euro 4			
Max. Engine Speed (rpm)	2,400			
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Valve, Water-cooled			
Combustion System	Direct Injection Type			
Fuel Injection System	Electronic Control Common Rail Type			
Displacement (L)	10.520			
PERFORMANCE				
Max. Output (PS) ISO	373			
Max. Torque (Nm) ISO	1,565			
Max. Speed (kph)	121			
SUSPENSION				
Front	Semi-elliptic Leaf Springs with Shock Absorbers and Stabilizer			
Rear	Semi-elliptic Leaf Springs with Torque Rods			
BRAKES				
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type			
(Features)	Leading and Trailing Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster and ABS			
Parking	Spring Brake Acting on Rear Wheels			



